



**WACKER
NEUSON**

DPU 7060SC Reversible Vibratory Plate, 70 kN, Remote Control

Item Number 0008927

Strong and smart: DPU 7060SC with stand-by mode

The DPU 7060SC features a stand-by mode and intelligent technology. Thanks to the innovative design, the machine will immediately go into idle running mode and stop all travel movements when the operator lets go of the joy sticks. In combination with the award-winning WACKER infrared remote control, this machine uses line of sight for added safety. Wear and environmental pollution are reduced as a consequence. Another feature makes the DPU 7060SC unique: it is the only machine in its class offering a virtual zero-loss V-belt technology.



Technical Data

Description	Metric	Imperial
Operating weight without extension plates	584 kg	1287.5 lb
Operating weight with standard extension plates	615 kg	1355.8 lb
Shipping weight (including packaging)	640 kg	1.411 lb
Working width (without extension plates)	600 mm	23.6 in
Working width (with extension plates)	770 mm	30.3 in
Machine height	795 mm	31.5 in
Shipping size (length)	1.250 mm	49.2 in
Shipping size (width)	870 mm	34.3 in
Shipping size (height)	1.000 mm	39.4 in
Base plate thickness	14 mm	0.55 in
Max. centrifugal force	69,0 kN	15,525 lb
Vibration frequency	51 Hz	51 vpm
Max. forward and reverse travel	25 m/min	82 ft/min

Max. compacted area - with standard extension plates (depending on soil)	1.050 m ² /h	11,298 ft ² /h
Gradeability	40 %	40 %
Drive engine	air-cooled, single-cylinder, diesel engine (non-EPA2 approved) with electric starter and automatic oil shut-off	
Manufacturer	Farymann	
Type	43 F	
Max. power output according to DIN-ISO 3046*	11,0 kW	14.8 hp
at	3.000 1/min	3,000 rpm
Rated power output	9,0 kW	12.1 hp
at	2.530 1/min	2,530 rpm
Fuel consumption	1,4 l/h	1.48 US qt/h
Fuel tank capacity	7,5 l	7.9 US qt
Max. allowable tilt of engine in continuous operation	15 °	15 °
Power Train	from drive engine via automatic centrifugal clutch directly to exciter	

Specifications may change due to continuous product development.

* Actual power output may vary due to conditions of specific use.

Accessories

Accessories are not included with machine purchase.

- 
0126289: Set of extension plates, 30 mm/1.18 "
- 
0125872: Set of extension plates, 85 mm/3.35 "
- 
0045183: Plate

Features and Benefits

- Innovative infrared remote control puts the machine in idle and stops the vibration if the operator comes too close to the sensing eye with the control box or loses visual contact with the machine.
- When compared to hydraulically driven machines the modern V-belt technology of the DPU 7060SC provides a consistently high degree of efficiency, power and durability.

- Retractable infrared sensing eye offers complete and effective protection against damages on the job site or during transport.
- Ergonomic design and intuitive handling of the remote control offer straightforward and simple operation.
- Equipped with a low oil shutdown device and a cyclonic air cleaner. The engine is extremely resistant to high or low temperatures and dust and requires minimum service.

Standard Package

- includes extension plates, remote control, operator's manual and parts book



To locate a Wacker Neuson representative near you, please visit our website at
www.wackergroup.com

© 2008 Wacker Construction Equipment AG